

TS-1572

Solid Ca-Zn Heat Stabilizer

Technical Information

Effective: 23 June 2016

TS-1572 is a very efficient solid calcium/zinc stabilizer for cable general purpose sheathing for 70-80°C Application.

Typical Properties of TS-1572

Physical State and Appearance	White powder
Bulk Density	0.39 +/- 0.05

These values are typical only and do not constitute a product specification

Features

TS-1572 imparts very good initial colour and long-term Heat stability and heat ageing properties.

Safety and Handling

Please refer to the MSDS, available on request.

Storage

Store in a cool and dry place. Once opened, the bag should be tightly closed after use.

The information contained herein relates to a specific Galata product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet shall be construed to modify any of Galata standard terms and conditions of sale under which the product is sold by Galata. NOTHING IN THIS TECHNICAL DATA SHEET SHALL BE CONSTRUED TO CONSTITUTE A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner.